



SOHO INDIGO ADHOC PRINT

face material Century Soho Indigo Adhoc Print is a range of adhesive papers certify for HP Indigo printing process.

		size	grain	substance	thickness μm ($\pm 5\%$)
range	Adhoc Symbol Freelifa Gloss	32x46,4	LG	192	170
	Adhoc Symbol Freelifa Satin	32x46,4	LG	192	177
	Adhoc Tintoretto Gesso	32x46,4	LG	197	225

HP Indigo certification



adhesive Modified acrylic adhesive in water-based emulsion. Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect foodcontacts and corresponding to UNI EN 71 “toys security” norms.

technical features	tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
	unit of measure	g/25 mm	hours	$^{\circ}\text{C}$	$^{\circ}\text{C}$
SUPERTACK	1200	3	+ 5	- 10	+ 80

backing material Single glazed and monosilicone coated white papers. Available only with crack-back.

technical features	substance	thickness	opacity	tensile strength	
	ref. standard/instrument	ISO 536	ISO 2471	ISO 1924	
unit of measure	g/m^2	μm	%	N/15 mm	
				long	trasv
	85	92	84	70	40

notes Special runs for sizes and/or other adhesives available upon request. The backing material is not certify for HP Indigo printing process.

The Company reserves the right to modify the technological features of the product in relation to market requirements.