



ARCOSSET LH

description

White uncoated papers certify FSC, made with E.C.F. pulp. Specifically manufactured with reduced moisture content (Low Humidity), for the web-offset print. Available in the White White shade. Good look-through and printing performance.

range

size	grain	substance			
-	LG	70	80	90	120

technical features
ref. standard/instrument
unit of measure

substance	VSA	opacity	roughness	tensile strength	
ISO 536	ISO 534	ISO 2471	ISO 8791-2	ISO 1924	
g/m ²	cm ³ /g	%	ml/min	KN/m	
				long±10%	cross±10%
70 ± 3%	1,2	88 ± 2	220 ± 30	3,9	2,6
80 ± 3%	1,2	90 ± 2	220 ± 30	4,5	2,8
90 ± 3%	1,2	92 ± 2	220 ± 30	5,2	3,2
120 ± 3%	1,2	95 ± 2	220 ± 30	6,5	3,9

Brightness (col. White White) - ISO 2470 (R457) 108% ± 2
Relative Humidity 38% ± 5 ref. TAPPI 502-98

ecological features



The mark of responsible forestry

ELEMENTAL
CHLORINE
FREE
GUARANTEED



notes

The product is completely biodegradable and recyclable. Arcosset LH is produced by special runs available upon request, and need a minimum lot of production.

The Company reserves the right to modify the technological features of the product in relation to market requirements.

Arcoset LH is a paper for publishing, note-books, calendars, catalogues, technical manuals, magazines.

applications

Arcoset LH is developed for the commercial web-offset print. Good results with Pantone and Metallic inks.

printing suggestions

Varnishing must be assessed in advance. The varnishing coated with an offset machine is almost fully absorbed and therefore does not improve gloss or protection. Screen-printing varnishing achieves better results, although it is often necessary to perform two shots to achieve a distinctly evident result. The plastic laminating is not recommended.

converting suggestions