



MURILLO

description Uncoated papers and boards made with E.C.F. pulp. Felt marked on both sides. Pulp-dyed with light-fast colours. Available in seventeen shades.

range

size	grain	substance
70x100	LG	190 260 360

technical features
ref. standard/instrument
unit of measure


substance	VSA	Wax pick test	Taber stiffness 15°	
ISO 536	ISO 534	UNI 9073	ISO 2493	
g/m ²	cm ³ /g	n° (Dennison)	mN	
			long±10%	trasv±10%
190 ± 4%	1,45	≥ 14	80	40
260 ± 5%	1,45	≥ 14	190	100
360 ± 5%	1,45	≥ 14	500	230

Brightness (col. Bianco) ISO 2470 (R457) - 91% ± 2
Relative Humidity 50% ± 5 ref. TAPPI 502-98

ecological features



ELEMENTAL
CHLORINE
FREE
GUARANTEED



notes The products could show light differences in papershade and look due to natural raw materials used. The product is completely biodegradable and recyclable. Special runs available upon request.

Fabriano is a trademark of Fedrigoni SpA
The Company reserves the right to modify the technological features of the product in relation to market requirements.

Murillo papers and boards are ideal for any kind of publishing, packaging and commercial printing. They are held in high regard for packaging, special publications, brochures, booklets, greeting-cards and coordinated graphic materials.

applications

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen printing. The macro-porous surface suggests the use of oxidative drying inks. The characteristic felt marking requires specific printing pressure settings. The Black shade, is made without the use of Carbon Black pigment. Are excluded oxidation problems or mottling for the hot foil stamping.

printing
suggestions

Varnishing and plastic laminating must be assessed in advance. The varnishing coated with an offset machine is almost fully absorbed and therefore does not improve gloss or protection. Screen-printing varnishing achieves better results, although it is often necessary to perform two shots to achieve a distinctly evident result. The surface roughness typical of felt marked papers may give rise to micro defects with plastic laminating caused by incomplete adhesion of the film to the substrate. Good results with major processing operations such as: cutting, die-cutting, scoring, folding and glueing.

converting
suggestions