



# SOHO INDIGO ADHOC PRINT

**face material** Century Soho Indigo Adhoc Print is a range of adhesive papers certify for HP Indigo printing process.

<b>range</b>		size	grain	substance	thickness $\mu\text{m}$ ( $\pm 5\%$ )
Adhoc Symbol Freelifa Gloss		32x46,4	LG	192	170
		33x48,2	LG	192	170
Adhoc Symbol Freelifa Satin		32x46,4	LG	192	177
		33x48,2	LG	192	170
Adhoc Tintoretto Gesso		32x46,4	LG	197	225

**HP Indigo certification** Certified for **HP Indigo**

**adhesive** Modified acrylic adhesive in water-based emulsion. Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect foodcontacts and corresponding to UNI EN 71 “toys security” norms.

<b>technical features</b>	tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
unit of measure	<i>g/25 mm</i>	<i>hours</i>	$^{\circ}\text{C}$	$^{\circ}\text{C}$	$^{\circ}\text{C}$
<b>SUPERTACK</b>	1200	3	+ 5	- 10	+ 80

**backing material** Single glazed and monosilicone coated white papers. Available only with crack-back.

<b>technical features</b>	substance	thickness	opacity	tensile strength	
ref. standard/instrument	<i>ISO 536</i>	<i>ISO 536</i>	<i>ISO 2471</i>	<i>ISO 1924</i>	
unit of measure	<i>g/m<sup>2</sup></i>	<i><math>\mu\text{m}</math></i>	<i>%</i>	<i>N/15 mm</i>	
				<i>long</i>	<i>trasv</i>
	85	92	84	70	40

**notes** Special runs for sizes and/or other adhesives available upon request. The backing material is not certify for HP Indigo printing process.

The Company reserves the right to modify the technological features of the product in relation to market requirements.