



SOHO INDIGO SPLENDORLUX

description One-side Cast Coated board, high gloss and whiteness. Certify FSC® and made with E.C.F. pulp. Light matt coating on reverse side. Available in Premium White colour. Century Soho Indigo Splendorlux 1 P.W. is certify for HP Indigo printing process.

range size grain substance
46,4x32 SG 250

technical features
ref. standard/instrument
unit of measure

substance	thickness	Taber stiffness 15°		tensile strength	
ISO 536	ISO 534	ISO 2493		ISO 1924	
g/m ²	µm	mN		kN/m	
	± 5%	long±10%	trasv±10%	long±10%	trasv±10%
250 ± 5%	290	170	80	17	7,8

Brightness ISO 2470 (R457) - 92% ± 2
Gloss - ISO 8254-2 - 98% ± 3
Relative Humidity 45% ± 5 ref. TAPPI 502-98

HP Indigo certification Certified for **HP Indigo**

ecological features



The mark of responsible forestry

ELEMENTAL CHLORINE FREE GUARANTEED



notes The product is completely biodegradable and recyclable. Special runs available upon request. Century Soho Indigo Splendorlux 1 P.W. is certify for HP Indigo printing process only on Cast Coated side. The light matt coating on reverse side, guarantee only the printing of minimum percentage of the ink (one color text).

The Company reserves the right to modify the technological features of the product in relation to market requirements